



# Graffiti Gobbler Paint Remover

Item Series #241601-01

U.S. Department Of Labor  
Occupational Safety And Health Administration  
**MATERIAL SAFETY DATA SHEET**  
Required Under USDL Safety And Health Regulations  
(29 CFP 1910.1200 "Hazards Communication Standard")

### Section I – Product Identification

**Manufactured For:** Gabriel First Corp.  
**Emergency Phone:** 1-800-424-9300  
**Address:** 233 W. Commercial Street, East Rochester, NY 14445  
**Product Name:** Graffiti Gobbler Paint Remover  
**Chemical Family:** Chemical Mixture  
**Prepared On:** 11/13/09

**Hazardous Material Description:**  
Paint Related Material, 8, UN3066, PGIII

### Section II – Product & Component Data

CHEMICAL NAMES	CAS NO.	% Weight	% V	Listed as Carcinogenin NTP, IARC, or OSHA 11910(z) (specify)
Ethylene Glycol-proply Ether	2807-30-9	10-40		NO
Potassium Hydroxide	1310-58-3	5-10		NO
Petroleum Solvent	64742-94-5	10-15		NO
Ethanolamine	141-43-5	5-10		NO
2-Heptanone	110-43-0	5-10		NO
Amyl Acetate	628-63-7	5-10		NO
2-Furyl Alcohol	98-00-0	5-10		NO
Petroleum Solvent	64742-81-0	1-5		NO

### Section III – Physical Data

**Boiling Point:** >212° F  
**Specific Gravity (H<sub>2</sub>O=1):** 0.97  
**Vapor Pressure:** 4 mm Hg  
**Percent, Volatile By Volume (%):** >99%  
**Physical Description:** Orange/yellow clear liquid.  
Fruity solvent odor.

**Vapor Density (Air=1):** >1  
**Evaporation Rate:** >1  
**Solubility In Water:** Forms an emulsion.  
**pH:** 13.0  
**Percent Solid by Weight (%):**  
**Material:** Liquid:  Solid:  Gas:  Paste:  Powder:

### Section IV – Fire and Explosion Hazard Data

**Flash Point/Method Used:** 120° F  
**Flammable Limits:** Not Determined  
**LEL: UEL:**  
**Extinguishing Media:** Foam, CO<sub>2</sub>, Dry Chemical

**Special Fire Fighting Procedures:** Wear self-contained breathing apparatus with full face piece operated in positive pressure mode.  
**Unusual Fire And Explosion Hazards:** Vapors are heavier than air, use water spray to reduce vapors.

### Section V – Health Hazard Data

**EFFECTS OF OVEREXPOSURE – CONDITIONS TO AVOID:**  
**Eyes:** Irritation, inflammation.  
**Skin:** Prolonged or repeated contact can cause dryness, irritation.  
**Ingestion:** Abdominal pain.  
**Inhalation:** High airborne concentrations may irritate respiratory tract and cause headache, nausea, and dizziness.  
**PRIMARY ROUTES OF ENTRY:**  Inhalation  Skin Contact

**EMERGENCY FIRST AID PROCEDURES:**  
**Eyes:** Flush with large amounts of water. Seek medical attention.  
**Skin:** Wash off with soap and water.  
**Inhalation:** Move to fresh air. Seek medical attention if effects are apparent.  
**Ingestion:** Drink several glasses of water or if large amounts have been ingested seek medical attention.



# Graffiti Gobbler Paint Remover

Item Series #241601-01

## Section VI – Reactivity Data

**Stability:** Stable

**Conditions To Avoid:** Strong oxidizing materials.

**Hazardous Decomposition Products:**

**Hazardous Polymerization:** Will not occur.

**Incompatibility (Materials To Avoid):** Strong oxidizing materials.

## Section VII – Spill or Leak Procedures

**Steps To Be Taken In Case Material Is Released Or Spilled:**

Dike and absorb with inert material. Drum up for disposal.

**Waste Disposal Method:**

Dispose in compliance with local, state, and federal regulations for ignitable waste.

**Cercia (Superfund) Reportable Quantity (in lbs.)**

**RCRA Hazardous Waste NO (40 CFR 261.33)**

**Volatile Organic Compound (VOC) (as packaged minus water)**

**Theoretical lb/gal**

**Analytical lb/gal**

## Section VIII – Special Protection Information

**Respiratory Protection (specify type):** NIOSH approved full face positive pressure respirator if TLV's are exceeded.

**Local Exhaust (specify rate):**

**Ventilation:** Adequate to maintain TLV's.

**Mechanical (General) (specify rate)**

**Other:**

**Protective Gloves:** Chemical resistant.

**Eye Protection:** Chemical goggles

**Other Protective Equipment:** None required.

## Section IX – Special Precautions

**Precautions To Be Taken In Handling And Storing:**

Store out of sunlight between 32° and 95° F.

**Other Precautions:**

Store away from heat, spark, flame, or other ignition source.

Keep tightly closed in original container.

KEEP OUT OF REACH OF CHILDREN.

*This information is given in good faith, but no warranty expressed or implied is made. Our company believes that it is accurate to the best of its knowledge and relates only to the specific material designated herein.*