

MATERIAL SAFETY DATA SHEET

Elite II High Gloss 8142-1710

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: Elite II HG PART A
PRODUCT NUMBER: 8142-1710

MANUFACTURED FOR: Gabriel First Corp.
STREET ADDRESS: 233 West Commercial St PO Box 191
CITY, STATE, ZIP: East Rochester, NY 14445-0191

INFORMATION PHONE: 800-873-2000
EMERGENCY PHONE: Chemtrec 800-424-9300

DATE REVISED: 8/29/2013

SECTION 2: HAZARDS IDENTIFICATION

HMIS HAZARD CLASSIFICATION

HEALTH: 1 FLAMMABILITY: 1 REACTIVITY: 0 PERSONAL PROTECTIVE EQUIPMENT: G

POTENTIAL HEALTH EFFECTS

EYES:

MATERIAL OR HIGH VAPOR CONCENTRATION CAN CAUSE IRRITATION TO THE EYES.

SKIN:

CAN CAUSE IRRITATION TO SKIN.

INGESTION:

LIQUID CAN CAUSE IRRITATION TO THE MUCOUS MEMBRANES IF SWALLOWED.

INHALATION:

HIGH VAPOR CONCENTRATION CAN CAUSE IRRITATION TO THE RESPIRATORY TRACT.

HEALTH HAZARDS (ACUTE AND CHRONIC):

PROLONGED OR REPEATED EXPOSURE MAY CAUSE ASTHMA AND SKIN SENSITIZATION OR OTHER ALLERGIC RESPONSES.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE:

RESPIRATORY CONDITIONS OR OTHER ALLERGIC AILMENTS. Repeated or prolonged exposure of high levels of solvents via inhalation and ingestion may affect the liver or central nervous system.

CARCINOGENICITY

OSHA: NO NTP: NO IARC: NO

ADDITIONAL CARCINOGENICITY INFORMATION:

CAS# 111-76-2: May contain trace components of benzene, toluene, ethylbenzene and NJTSRN 800963-5170 and contains chemicals known to the state of California to cause cancer and birth defects.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

<u>INGREDIENT</u>	<u>CAS NO.</u>	<u>OSHA PEL</u>	<u>ACGIH TLV</u>	<u>OSHA STEL</u>	<u>WEIGHT %</u>
Triethanolamine	102-71-6	none	5mg/m3	none	<1.0
Propylene glycol n-butyl ether	5131-68-8	none	none	none	<3.0
Water	7732-18-5	none	none	none	45-65
Polyacrylate resin	trade secret	none	none	none	25-50
Reactive diluent	trade secret	none	none	none	<3.0
Dipropylene glycol methyl ether acetate	88917-22-0	none	none	none	<4.0
dipropylene glycol monomethyl ether	34590-94-8	100ppm	150ppm	600ppm	<0.5
*2-butoxyethanol	111-76-2	50ppm	20ppm	none	<0.5
2-ethyl-1-hexanol	104-76-7	none	none	none	<0.5
naphtha, petroleum, heavy	64742-82-1	none	none	none	<0.5
2,5,8,11 tetramethyl 6 dodecyn-5,8 diol ethoxylate	169117-72-0	none	none	none	<1.0
additive	NJTSRN 800963-5023	none	none	none	

SECTION 3 NOTES: (*) TOXIC CHEMICAL(S) SUBJECT TO THE REPORTING REQUIREMENTS OF SECTION 313 OF TITLE III AND OF 40 CFR 372 ARE PRESENT.

MATERIAL SAFETY DATA SHEET

Elite II High Gloss 8142-1710

SECTION 4: FIRST AID MEASURES

EYES:

IMMEDIATELY FLUSH WITH LARGE AMOUNTS OF WATER FOR AT LEAST FIFTEEN MINUTES WHILE LIFTING UPPER AND LOWER LIDS. GET IMMEDIATE MEDICAL ATTENTION.

SKIN: FLUSH SKIN WITH WATER FOR AT LEAST 15 MINUTES AND REMOVE ALL CONTAMINATED CLOTHING IMMEDIATELY. GET MEDICAL ATTENTION IF REDDENING OR SWELLING OCCURS.

INGESTION:

DO NOT INDUCE VOMITTING. INGESTION OR VOMITTING MAY CAUSE ASPIRATION INTO THE LUNGS RESULTING IN CHEMICAL PNEUMONITIS.

INHALATION:

REMOVE VICTIM TO FRESH AIR IF EFFECTS PERSIST AND ADMINISTER OXYGEN IF NECESSARY.

NOTES TO PHYSICIANS OR FIRST AID PROVIDERS:

SECTION 5: FIRE-FIGHTING MEASURES

FLAMMABLE LIMITS IN AIR, UPPER: not available
(% by volume) LOWER: not available

FLASH POINT: >200°F

METHOD USED:

SETA FLASH

EXTINGUISHING MEDIA:

FOAM, ALCOHOL FOAM, CO2, DRY CHEMICAL, WATER FOG

SPECIAL FIRE FIGHTING PROCEDURES:

TOXIC FUMES WILL BE EVOLVED WHEN THIS MATERIAL IS INVOLVED IN A FIRE. A SELF CONTAINED BREATHING APPARATUS SHOULD BE AVAILABLE FOR FIRE FIGHTERS. COOL ALL FIRE EXPOSED CONTAINERS WITH WATER.

UNUSUAL FIRE AND EXPLOSION HAZARDS:

NONE KNOWN.

SECTION 6: RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

AVOID CONTACT WITH MATERIAL. WEAR THE APPROPRIATE SAFETY EQUIPMENT. STOP SPILL AT SOURCE, DYKE AREA TO PREVENT SPREADING. PUMP LIQUID TO SALVAGE TANK. TAKE UP THE REMAINDER WITH AN ABSORBENT SUCH AS CLAY AND PLACE IN DISPOSAL CONTAINERS.

SECTION 7: HANDLING AND STORAGE

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:

AVOID ALL SKIN CONTACT. AVOID BREATHING VAPORS. RESEAL PARTIALLY USED CONTAINERS. PROPERLY LABEL ALL CONTAINERS. WASH WITH SOAP AND WATER BEFORE EATING, DRINKING, SMOKING, OR USING TOILET FACILITIES. OBSERVE GOOD INDUSTRIAL HYGIENE AND SAFE WORKING PRACTICES.

OTHER PRECAUTIONS:

MIXED MATERIALS CONTAIN THE HAZARDS OF ALL THE COMPONENTS, THEREFORE, READ THE MSDS OF ALL COMPONENTS TO BECOME FAMILIAR WITH ALL HAZARDS PRIOR TO USING THIS PRODUCT.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

RESPIRATORY PROTECTION:

NONE REQUIRED UNDER NORMAL CONDITIONS OF USE. NIOSH APPROVED AIR-SUPPLIED RESPIRATOR DURING THE CLEANING, HIGH TEMPERATURE PROCESSING OR WHEN THERMAL DECOMPOSITION IS SUSPECTED.

VENTILATION:

AVOID BREATHING VAPORS. VENTILATION MUST BE SUFFICIENT TO CONTROL VAPORS

PROTECTIVE GLOVES:

IMPERVIOUS GLOVES – NEOPRENE OR RUBBER

EYE PROTECTION:

SPLASH PROOF GOGGLES OR SAFETY GLASSES WITH SIDE SHIELDS

OTHER PROTECTIVE CLOTHING OR EQUIPMENT:

CLEAN BODY COVERING CLOTHING AS WELL AS APRON, FOOTWEAR EQUIPMENT SHOULD BE USED AS DEEMED NECESSARY TO AVOID CONTACT WITH THE MATERIAL.

WORK HYGIENIC PRACTICES:

OBSERVE GOOD GENERAL HYGIENIC PRACTICES.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE AND ODOR: low viscosity liquid – milky white color – NEGLIGIBLE ODOR
BOILING POINT OR RANGE: N/A
VAPOR DENSITY (AIR = 1): N/A
SPECIFIC GRAVITY (H₂O = 1): 1.08
EVAPORATION RATE: N/A
SOLUBILITY IN WATER: emulsifiable/miscible

SECTION 10: STABILITY AND REACTIVITY

STABILITY:
STABLE CONDITIONS TO AVOID (STABILITY):
AVOID CONTACT WITH OPEN FLAMES AND ALL SOURCES OF IGNITIONS AND SPARKS. Protect from freezing.
INCOMPATIBILITY (MATERIAL TO AVOID):
AVOID CONTACT WITH STRONG OXIDIZING AGENTS OR MATERIALS.
HAZARDOUS DECOMPOSITION OR BY-PRODUCTS:
CARBON MONOXIDE, CARBON DIOXIDE AND NITROGEN COMPOUNDS.
HAZARDOUS POLYMERIZATION:
WILL NOT OCCUR.

SECTION 11: TOXICOLOGICAL INFORMATION

additive NJTSRN 800963-5023: Acute oral toxicity: LD50 rat>8,000,000 mg/kg; skin irritation rabbit – no skin irritation
 2,5,8,11 tetramethyl 6 dodecyn-5,8 diol ethoxylate CAS# 169117-72-0: LD50 Ingestion >2000 mg/kg – rat; Dermal LD 50 >2000 mg/kg – rabbit; severe eye irritant; mild skin irritant; Not mutagenic in Ames test.
CAS# 111-76-2:: Acute oral Toxicity -LD50 rat 530 mg/kg; LD50 rabbit 520 mg/kg; Acute dermal Toxicity LD50 Rabbit 100mg/kg; Acute Inhalation Toxicity LC50 rat 468ppm (4h); Skin Irritation rabbit – moderate skin irritation.; Eye irritant - rabbit
CAS# 104-76-7: Acute Oral Toxicity: LD50 rat >5000mg/kg.; Acute Dermal Toxicity rabbit 1970 mg/kg.; Skin Irritation rabbit – moderate skin irritation.; severe eye irritant - rabbit
CAS# 64742-82-1: Acute Oral Toxicity LD50 >5000 mg/kg; Acute Dermal Toxicity LD50 rabbit >3000 mg/kg; Acute inhalation Toxicity LC50 rat >11.6 mg/l; Skin Irritation rabbit – moderate skin irritation.; Eye Irritant – Rabbit.
CAS# 34590-94-8:Acute Oral Toxicity (LD50) 5130 mg/kg rat; Acute Dermal Toxicity (LD50) 9500 mg/kg rabbit; May cause damage to the liver, central nervous system. Hazardous in case of ingestion or inhalation. Slight skin irritant. Eye contact can cause corneal irritation.
Dipropylene glycol methyl ether acetate CAS# 88917-22-0: is toxic to lungs, is very hazardous in case of ingestion, is hazardous in case of skin contact (irritant, permeator), of inhalation.
Polyacrylate resinCAS# trade secret: Acute oral toxicity LD50 > 2000mg/kg (rat); Skin irritation – (4h) no skin irritation; Eye irritation – rabbit, slightly irritating. Mutagenicity, Genetic Toxicity in Vitro: Ames – negative.
Propylene glycol n-butyl ether CAS# 5131-68-8: Acute Oral Toxicity LD50 – 1900 mg/kg rat; Acute Dermal Toxicity LD50 3100 mg/kg rabbit; Skin Irritation – irritating (rabbit); Eye Irritation rabbit – irritating. Repeated Dose Toxicity: 11 d, inhalation NOAEL <600 ppm (rat). Biodegradation >90% exposure time 28 d; Acute Toxicity to Aquatic Vertabraes EC50 . 1000 mg/ml (water flea)
Triethanolamine CAS# 102-71-6: Acute Oral Toxicity LD50 4190 mg/kg (rat); Acute Dermal Toxicity LD50 >2000 mg/kg (rabbit); Skin Irritation (rabbit) slightly irritating. Eye Irritation (rabbit) irritating. Repeated Dose Toxicity 28 days, inhalation NOAEL: > 0.5 mg/ml (rat, male/female, 6hrs/day 5 days/week and 13 weeks, dermal: NOAEL: 500mg/kg (rat, male/female, daily)

SECTION 12: ECOLOGICAL INFORMATION

2,5,8,11 tetramethyl 6 dodecyn-5,8 diol ethoxylate CAS# 169117-72-0: This product is anticipated to be harmful to aquatic organisms based on data from similar product.
Polyacrylate resinCAS# trade secret: Acute and Prolonged Toxicity to fish LC50 > 100mg/ml (Zebra Fish) 96 hr;
Triethanolamine CAS# 102-71-6: Biodegradation: Aerobic, 82% exposure time 8 days, inherently biodegradable. Biological Oxygen demand (BOD) 0.5 mg/g; Acute and Prolonged Toxicity to fishLC50 >5000 mg/ml (fathead minnow), 96 h; Acute Toxicity to Aquatic Invertebrates EC50: 216-750 mg/l end point (green algae), 72 hr.
Propylene glycol n-butyl ether CAS# 5131-68-8: Boidegradation >90% exposure time 28 d; Acute and Prolonged Toxicity to Fish LC50: 560-1000 mg/l (guppy); Acute Toxicity to Aquatic Invertebrates EC50 >1000 mg/l (water Flea)

SECTION 13: WASTE DISPOSAL

WASTE DISPOSAL METHOD:.
DISPOSE OF THE MATERIAL IN A WASTE DISPOSAL SITE IN ACCORDANCE WITH LOCAL, STATE, AND FEDERAL LAW.

SECTION 14: Transport Information

DOT: Not Regulated

IMO/IMDG: Not Regulated

SECTION 15: REGULATORY INFORMATION

additive NJTSRN 800963-5023: on TSCA List. Not a California Prop 65 chemical

CAS# 111-76-2: Section 313 toxic Chemical. Section 311 hazard category – Chronic, fire, On TSCA list. May contain trace components of benzene, toluene, ethylbenzene and NJTSRN 800963-5170 and contains chemicals known to the state of California to cause cancer and birth defects. All components on the DSL Canada

CAS# 104-76-7: - on TSCA list and on Canada DSL

CAS# 64742-82-1 – on TSCA and on Canada DSL

CAS# 34590-94-8: Is on the Canadian DSL (class B-3 combustible liquid), TSCA list and European inventory of existing commercial chemical substances. Dipropylene glycol monomethyl ether TSCA 4(a) proposed test rules: Dipropylene glycol monomethyl ether TSCA 8(d) and S data reporting: Dipropylene glycol monomethyl ether: effective 4/13/89: Sunset Date: 6/30/98

Dipropylene glycol methyl ether acetate CAS# 88917-22-0: DSCL (EEC) R36 – irritating to skin- risk of serious damage to eyes. WHIMS Class B-3

Polyacrylate resin CAS# trade secret: Listed on TSCA.

Propylene glycol n-butyl ether CAS# 5131-68-8: Listed on TSCA

Triethanolamine CAS# 102-71-6: Listed on TSCA

Reactive diluent CAS# trade secret: On New Jersey, Massachusetts and Pennsylvania right to know lists at > 1%

SECTION 16: OTHER INFORMATION

DISCLAIMER: The information Contained herein is based on the data available and is believed to be accurate, However, the manufacturer makes no warranty expressed or implied regarding the accuracy of this data or the results obtained from the use thereof. Accordingly, we assume no responsibility for injury from the use of this product.

MATERIAL SAFETY DATA SHEET

Elite II High Gloss 8142-1710

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: Elite II HG PART B
PRODUCT NUMBER: 8142-1710

MANUFACTURED FOR: Gabriel First Corp.
STREET ADDRESS: 233 West Commercial St PO Box 191
CITY, STATE, ZIP: East Rochester, NY 14445-0191

INFORMATION PHONE: 800-873-2000
EMERGENCY PHONE: Chemtrec 800-424-9300

DATE REVISED: 2/1/12

SECTION 6: HAZARDS IDENTIFICATION

HMIS HAZARD CLASSIFICATION

HEALTH: 2 FLAMMIBILITY: 2 REACTIVITY: 1 PERSONAL PROTECTIVE EQUIPMENT: G

POTENTIAL HEALTH EFFECTS

Warning - Combustable Liquid, eye and respiratory tract irritant. Harmful if inhaled. Possible sensitizer. Reacts with common materials including water, alcohols, and amines releasing large amounts of carbon dioxide.

EYES:

CAN CAUSE SEVERE IRRITATION, REDNESS, TEARING, OR BLURRED VISION AS WELL AS CORNEAL OPACITY AND CONJUNCTIVITIS. MAY CAUSE TEMPORARY CORNEAL INJURY.

SKIN:

MAY CAUSE IRRITATION, DEFATTING AND DERMATITIS. MAY CAUSE SENSITIZATION. PERSONS PREVIOUSLY SENSITIZED CAN EXPERIENCE ALLERGIC SKIN REACTION.

INGESTION:

CAN CAUSE GASTROINTESTINAL IRRITATION, NAUSEA, VOMITTING, DIARRHEA. ASPIRATION OF MATERIAL INTO THE LUNGS CAN CAUSE CHEMICAL PNEUMONITIS WHICH CAN BE FATAL. CAN CAUSE CORROSIVE ACTION TO THE MUCOUS MEMBRANES AND DIGESTIVE TRACTS.

INHALATION:

CAN CAUSE NAUSEA AND RESPIRATORY IRRITATION, DIZZINESS, WEAKNESS, FATIGUE, HEADACHE, AND POSSIBLE UNCONSCIOUSNESS. BURNING SENSATION TO MUCOUS MEMBRANES, SHORTNESS OF BREATH AND FLU LIKE SYMPTOMS MAY OCCUR. AS A RESULT OF PREVIOUS EXPOSURES, CERTAIN INDIVIDUALS MAY DEVELOP SENSITIZATION TO DIISOCYANATES, WHICH MAY CAUSE THEM TO REACT TO A LATER EXPOSURE. SYMPTOMS INCLUDE CHEST TIGHTNESS, WHEEZING, COUGH, SHORTNESS OF BREATH, OR ASTHMATIC ATTACK. EXTREME ASTHMATIC ATTACKS CAN BE LIFE THREATENING.

HEALTH HAZARDS (ACUTE AND CHRONIC):

CAN CAUSE SENSITIZATION BY EXPOSURE THROUGH CONTACT OR HIGH CONCENTRATIONS OF VAPOR. OVER-EXPOSURE TO THIS MATERIAL CAN CAUSE CARDIAC ABNORMALITIES. OVEREXPOSURE CAN POSSIBLY CAUSE ANEMIA, LIVER ABNORMALITIES, KIDNEY DAMAGE, OR EYE DAMAGE. MAY CAUSE ASTHMA OR OTHER RESPIRATORY DISORDERS, BRONCHITIS, EMPHYSEMA, HYPERACTIVITY, AND ECZEMA.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE:

RESPIRATORY CONDITIONS OR OTHER ALLERGIC AILMENTS

CARCINOGENICITY

OSHA: NO NTP: NO IARC: NO

ADDITIONAL CARCINOGENICITY INFORMATION: NO LISTED INGREDIENTS OF THIS PRODUCT ARE REGULATED AS CARCINOGENS.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

<u>INGREDIENT</u>	<u>CAS NO.</u>	<u>OSHA PEL</u>	<u>ACGIH TLV</u>	<u>OSHA STEL</u>	<u>WEIGHT %</u>
HEXANE, 1,6-DIISOCYANATE-, HOMOPOLYMER	28182-81-2	1 mg/ cu m	NONE	NONE	<50
BUTOXYL ISOPHORONE DIISOCYANATE HOMOPOLYMER	4435-53-4	NONE	NONE	NONE	20-30
POLYOXYETHYLENE TRIDECYL ETHER PHOSPHATE	5388-05-0	NONE	NONE	NONE	<20
DIMETHYLCYCLOHEXYLAMINE	9046-01-9	NONE	NONE	NONE	5-10
*ISOPHORONE DIISOCYANATE	98-94-2				1-3
*HEXANE, 1,6-DIISOCYANATO-	4098-71-9	0.005 ppm	0.0005 ppm	NONE	<0.50
	822-06-0	NONE	.005 PPM	NONE	<0.50

(*) Indicates toxic chemicals subject to the reporting requirements of section 313 of Title III and of 40 CFR 372 are present.

MATERIAL SAFETY DATA SHEET

Elite II High Gloss 8142-1710

SECTION 4: FIRST AID MEASURES

EYES:

IMMEDIATELY FLUSH WITH LARGE AMOUNTS OF WATER FOR AT LEAST 15 MINUTES. GET IMMEDIATE MEDICAL ASSISTANCE.

SKIN:

FOR EXTREME EXPOSURE USE A SAFETY SHOWER IMMEDIATELY. WASH AFFECTED AREA WITH SOAP AND WATER AND REMOVE CONTAMINATED CLOTHING PROMPTLY.

INGESTION:

DO NOT INDUCE VOMITING KEEP PERSON WARM AND CONSULT A PHYSICIAN IMMEDIATELY. GIVE 1-2 CUPS OF MILK OR WATER TO DRINK.

INHALATION:

REMOVE TO FRESH AIR IF EFFECTS PERSIST AND ADMINISTER OXYGEN IF NECESSARY. OBTAIN MEDICAL ASSISTANCE. ASTHMATIC TYPE SYMPTOMS MAY OCCUR IMMEDIATELY OR BE DELAYED FOR SEVERAL HOURS.

NOTES TO PHYSICIANS OR FIRST AID PROVIDERS:

EYES: STAIN FOR EVIDENCE OF CORNEAL INJURY. IF CORNEA IS BURNED, INSTILL ANTIBIOTIC/STEROID PREPARATION AS NEEDED. WORKPLACE VAPORS COULD PRODUCE REVERSABLE CORNEAL EPITHELIAL EDEMA IMPAIRING VISION. SKIN: THIS COMPOUND IS A SKIN SENSITIZER. TREAT SYMPTOMATICALLY AS FOR CONTACT DERMATITIS OR THERMAL BURN. INGESTION: TREAT SYMPTOMATICALLY. THERE IS NO SPECIFIC ANTIDOTE. INDUCING VOMITING IS CONTRAINDICATED BECAUSE OF THE IRRITATING NATURE OF THE COMPOUND. INHALATION: TREATMENT IS ESSENTIALLY SYMPTOMATIC. AN INDIVIDUAL HAVING A DERMAL OR PULMONARY SENSITIZATION REACTION SHOULD BE REMOVED FROM FURTHER EXPOSURE TO ANY ISOCYANATE.

SECTION 5: FIRE-FIGHTING MEASURES

FLAMMABLE LIMITS IN AIR, UPPER: N/A
(% by volume) LOWER: N/A

FLASH POINT: 168F

METHOD USED:

CLOSED CUP

EXTINGUISHING MEDIA:

FOAM, ALCOHOL FOAM, CO2, DRY CHEMICAL

SPECIAL FIRE FIGHTING PROCEDURES:

ENTER CONFINED AREA WITH FULL BUNKER GEAR INCLUDING A POSITIVE PRESSURE SELF-CONTAINED BREATHING APPARATUS. DURING A FIRE, HDI VAPORS AND OTHER HIGHLY TOXIC VAPORS MAY BE GENERATED. WATER OR EXTREME HEAT MAY CAUSE CONTAINERS TO EXPLODE.

UNUSUAL FIRE AND EXPLOSION HAZARDS:

WATER CONTAMINATION MAY CAUSE THE GENERATION OF CO2 AND CAUSE CONTAINER TO BURST OR EXPLODE. EXTREME HEAT MAY CAUSE CONTAINER TO EXPLODE. HAZARDOUS DECOMPOSITION PRODUCTS EVOLVED IN A FIRE MAY BE IRRITATING OR TOXIC.

SECTION 6: RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

WEAR RESPIRATOR AND PROTECTIVE CLOTHING. REMOVE ALL SOURCES OF IGNITIONS. REMOVE EXCESS WITH SPARK PROOF EQUIPMENT, AND THE REMAINDER WITH AN ABSORBENT SUCH AS CLAY AND PLACE IN DISPOSAL CONTAINERS. SEALING THE CONTAINER MAY LEAD TO RUPTURE AS ANY CONTAMINATED ISOCYANATE CAN REACT FORMING CO2. CONTAINED AIR RESPIRATOR MAY BE NECESSARY. EVACUATE AND ISOLATE SPILL AREA. VENTILATE CLOSED SPACES BEFORE ENTERING. CLEAN UP SPILL AREA WITH DECONTAMINATING SOLUTION MADE UP OF 50% ISOPROPNOL, 45% WATER AND 5% AMMONIA SOLUTION.

SECTION 7: HANDLING AND STORAGE

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:

STORE IN COOL DRY PLACE, SEAL ALL PARTIALLY USED CONTAINERS. WASH WITH SOAP AND WATER BEFORE EATING, DRINKING, SMOKING, OR USING THE TOILET FACILITIES. MIXED MATERIALS CONTAIN THE HAZARDS OF ALL THE COMPONENTS, THEREFORE, READ THE MSDS'S OF ALL THE COMPONENTS PRIOR TO USING MATERIAL. PROPERLY LABEL ALL CONTAINERS. KEEP MATERIAL AWAY FROM ALL SOURCES OF IGNITION.

OTHER PRECAUTIONS:

AVOID ALL SKIN CONTACT. AVOID BREATHING VAPORS GENERATED FROM THE MATERIAL. OBSERVE CONDITIONS OF GOOD GENERAL HYGIENE AND SAFE WORKING PRACTICES. CONTAMINATED LEATHER ARTICLES CANNOT BE CLEANED AND MUST BE DISCARDED IF CONTAMINATED WITH THIS PRODUCT. WASH ALL CONTAMINATED CLOTHING PRIOR TO THE REUSE THEROF. WEAR APPROPRIATE SAFETY EQUIPMENT AND RESPIRATOR AT ALL TIMES WHEN VENTILATION IS NOT SUFFICIENT TO CONTROL VAPORS. OBSERVE OSHA REGULATIONS FOR RESPIRATOR USE (29 CFR 1910.134). WHEN SPRAYING MATERIAL AVOID EXPOSURE TO ALL MISTS GENERATED BY USING AIR SUPPLIED RESPIRATOR. AVOID CONTACT WITH WATER.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

MATERIAL SAFETY DATA SHEET

Elite II High Gloss 8142-1710

RESPIRATORY PROTECTION:

USE A NIOSH APPROVED RESPIRATOR AS REQUIRED TO PREVENT OVER-EXPOSURE TO VAPOR IN ACCORDANCE WITH 29 CFR 1910.134. ENGINEERING OR ADMINISTRATIVE MEASURES SHOULD BE TAKEN TO REDUCE THE RISK & EXPOSURE. USE A POSITIVE PRESSURE SUPPLIED AIR RESPIRATOR WHEN EXCEEDING TLV'S OR IF HDI MONOMER CONCENTRATIONS EXCEED ACCEPTABLE LIMITS OR WHEN SPRAYING MATERIAL.

VENTILATION:

EXHAUST VENTILATION SUFFICIENT TO KEEP AIRBORN CONCENTRATIONS OF HDI BELOW THEIR TLV AND MGL MAXIMUM. REFERS TO PATTY'S INDUSTRIAL HYGIENE & TOXICOLOGY- VOLUME 1 (3RD EDITION) CHAPTER 17 AND VOLUME III (1ST EDITION) CHAPTER 3 FOR DETAILS.

PROTECTIVE GLOVES:

IMPERVIOUS GLOVES, NEOPRENE OR RUBBER.

EYE PROTECTION:

SPLASH PROOF GOGGLES OR SAFETY GLASSES WITH SIDE SHIELDS. DO NOT WEAR CONTACT LENSES WHEN USING THIS PRODUCT.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT:

CLEAN BODY COVERING CLOTHING AS WELL AS APRON FOOTWEAR OR OTHER EQUIPMENT SHOULD BE USED AS DEEMED NECESSARY TO AVOID CONTACT WITH THE MATERIAL.

WORK HYGIENIC PRACTICES:

OBSERVE GENERAL GOOD HYGIENIC PRACTICES.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE AND ODOR: PALE YELLOW LIQUID WITH NEGLIGIBLE ODOR

BOILING POINT OR RANGE: >212F

VAPOR DENSITY (AIR = 1): NOT AVAILABLE

SPECIFIC GRAVITY (H₂O = 1): 1.08

FLASH POINT: 365F

EVAPORATION RATE: N/A

SOLUBILITY IN WATER: NEGLIGIBLE

SECTION 10: STABILITY AND REACTIVITY

STABILITY:

STABLE UNDER NORMAL HANDLING AND STORAGE CONDITIONS.

CONDITIONS TO AVOID (STABILITY):

AVOID EXCESSIVE HEAT OR OPEN FLAMES AS WELL AS ALL SOURCES OF IGNITIONS SUCH AS SPARKS, HEATERS, STATIC DISCHARGES, ETC.

INCOMPATIBILITY (MATERIAL TO AVOID):

AVOID WATER, AMINES, STRONG BASES, ALCOHOLS, METAL COMPOUNDS, AND SURFACE ACTIVE COMPOUNDS.

HAZARDOUS DECOMPOSITION OR BY-PRODUCTS:

MAY FORM TOXIC CHEMICALS, CARBON MONOXIDE, CARBON DIOXIDE, OXIDES OF NITROGEN, HCN AND HDI.

HAZARDOUS POLYMERIZATION:

MOISTURE OR MATERIALS THAT REACT WITH ISOCYANATES AND TEMPERATURES ABOVE 400 DEGREES F MAY CAUSE POLYMERIZATION.

SECTION 11: TOXICOLOGICAL INFORMATION

Homopolymer of hexamethylene - Acute Oral Toxicity: LD50 > 5000 mg/kg (rat)

Acute inhalation Toxicity: No data available

Acute Dermal Toxicity: No data available

1,6-hexamethylene diisocyanate: Skin Irritation: Skin – sensitization, guinea pig. Sensitizing

Homopolymer of hexamethylene diisocyanate Skin irritation rabbit, irritating

Homopolymer of hexamethylene diisocyanate: Eye Irritation: rabbit, Draize, slightly irritating

Acute respiratory irritation: lung irritation (qualitative), human. Slightly irritating to moderating irritating.

Chronic Toxicity: This product does not contain any substances that are considered by OSHA, NTP, IARC, or ACGIH to be “probable” or “suspected” human carcinogens.

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicological information: No data available

Chemical fate information: No data available

MATERIAL SAFETY DATA SHEET

Elite II High Gloss 8142-1710

SECTION 13: WASTE DISPOSAL

WASTE DISPOSAL METHOD:
DISPOSE OF MATERIAL AS A HAZARDOUS WASTE ACCORDING TO FEDERAL, STATE, AND LOCAL REGULATIONS.

SECTION 14: Transport Information

DOT: Not regulated

IMO/IMDG: NA1993, COMBUSTIBLE LIQUID N.O.S. (CONTAINS Butoxyl), 3, PG III

SECTION 15: REGULATORY INFORMATION

OSHA Hazcom standard Rating: Fire Hazard; Acute health hazard and chronic health hazard.

All ingredients are on the TSCA list and Canadian DSL inventory

SARA Extremely Hazardous Substances (EHS) CERCLA Hazardous Substances: Isophorone diisocyanate (Sarah EHS TPQ) 500 lbs.

Hexane 1,6-diisocyanateo- CERCLA/SARA RQ 100 lbs.

This product may contain trace amounts of the following components that are regulated under California Proposition 65: Dioxane (cancer list), Acetaldehyde (Cancer list), Ethylene oxide (Cancer list, Reprod. List)

SECTION 16: OTHER INFORMATION

DISCLAIMER: THE INFORMATION HERE IN IS BASED ON THE DATA AVAILABLE AND IS BELIEVED TO BE ACCURATE, HOWEVER, THE MANUFACTURER MAKES NO WARRANTY EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF THIS DATA OR THE RESULTS OBTAINED FROM THE USE THEREOF. ACCORDINGLY, WE ASSUME NO RESPONSIBILITY FOR INJURY FROM THE USE OF THIS PRODUCT.